



NOTES:

1. SUBSTRATE:  
Fused Silica
2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO  $\leq 3$  ARCMIN
3. COATING (APPLY ACROSS CLEAR APERTURE)  
S1: NONE  
  
S2: NONE

4.  ARROW ON EDGE POINTING TOWARDS SURFACE S1


5.  FINE GRIND SURFACE



**FOR INFORMATION ONLY; DO NOT MANUFACTURE PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE  
DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2
SHAPE	PLANO	PLANO
SURFACE ACCURACY AT 632.8nm	$\lambda/10$	N/A
SURFACE QUALITY	60-40	COMMERCIAL POLISH
CLEAR APERTURE	Ø 228.60	Ø 228.60
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED

THIRD ANGLE PROJECTION 

ALL DIMS IN

mm

 **Edmund Optics®**

TITLE

254mm Dia.  $\lambda/10$  Fused Silica Optical Flat

DWG NO

46715000

SHEET  
1 OF 1