NOTES:

1. SUBSTRATE
2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN 5 arcsec
3. COATING (APPLY ACROSS COATING APERTURE)
   ENVIRONMENTAL DURABILITY:
   PHYSICAL DURABILITY:
   PERFORMANCE SPECIFICATIONS:
   T(avg): >85% FROM 520 - 1600nm FOR RANDOM POLARIZATION @ 45° AOI
   T(abs): >80% FROM 520 - 1600nm FOR ALL POLARIZATIONS @ 45° AOI
   R(avg): >97% FROM 350 - 480nm FOR RANDOM POLARIZATION @ 45° AOI
   R(abs): >95% FROM 350 - 480nm FOR ALL POLARIZATIONS @ 45° AOI
   T(abs): = 50% 500nm @ 45° AOI

   S1: HARD COATED
   S2: SINGLE LAYER MgF2

4. FINE GRIND SURFACE
5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
6. TRANSMITTED WAVEFRONT DISTORTION RMS@ 632.8nm ≤ ¼ λ
7. ROHS COMPLIANT

FOR INFORMATION ONLY:
DO NOT MANUFACTURE PARTS TO THIS DRAWING







LONGPASS FILTER

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
CLEAR APERTURE	22.0 x 32.0	22.0 x 32.0
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

Edmund Optics®

THIRD ANGLE PROJECTION

TITLE: 25.2 x 35.6mm, 500nm DICHROIC LONGPASS FILTER

ALL DIMS IN: mm

DWG NO: 69899

SHEET 1 OF 1