NOTES:

1. SUBSTRATE MATERIAL: **FUSED SILICA**

2. CENTERING TOLERANCE (AT 587.6nm):

PLANO AXIS WEDGE: < 3 ARCMIN POWER ASIX WEDGE: < 3 ARCMIN

AXIAL TWIST: < 3 ARCMIN


COATING (APPLY ACROSS CLEAR APERTURE)


S1: NONE S2: NONE

FINE GROUND SURFACE


POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICAIONS APPLY ACROSS CLEAR APERTURE

ROHS COMPLIANT





1 OF 1



PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

. / ((10 10 11))) DI () (I) (I)		
REV. A	\$1	\$2	
SHAPE	CONCAVE	PLANO	
SURFACE QUALITY	40 - 20	40 - 20	
CLEAR APERTURE	24.40 x 24.40	24.40 x 24.40	
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED	

	•		
	THIRD ANGLE	ф <u>п</u>	TIT
	THIRD ANGLE PROJECTION	4 -	""
<u> </u>	ALL DIMS IN	mm	DV

	Edmund Optics®
TITLE	LENS CYL SHAPING 25.4mm SQ x -75mm UNCTD

PROJECTION	Ψ				
ALL DIMS IN	mm	DWG NO	36096		SHEET 1 OF 1