## NOTES:


1. SUBSTRATE MATERIAL: N-BK7


2. COATING (APPLY ACROSS CLEAR APERTURE)

\$1 & \$2: MgF2 (400-700nm) R(AVG) ≤1.75% @ 400 - 700nm

3. FINE GROUND SURFACE

4. Rohs Compliant





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

|                 | \$1                  | \$2                  | EFL                    | 75.00 |        | <b>B</b> <sup>®</sup> Edmund Optics <sup>®</sup>   |
|-----------------|----------------------|----------------------|------------------------|-------|--------|--|
| SHAPE           | CONVEX               | PLANO                | BFL                    | 73.68 |        |  |
| RADIUS          | 38.76                | INFINITY             | THIRD ANGLE PROJECTION |       | TITLE  | 12.5mm DIA X 75mm FL MGF2 COATED,<br>CYLINDER LENS |
| SURFACE QUALITY | 60-40                | 60-40                |                        |       |        |  |
| CLEAR APERTURE  | Ø11.50               | Ø11.50               |                        |       |        |  |
| BEVEL           | PROTECTIVE AS NEEDED | PROTECTIVE AS NEEDED | ALL DIMS IN            | mm    | DWG NO | 48355 SHEET 1 OF 1                                 |