## NOTES:

- 1. SUBSTRATE MATERIAL: ALUMINUM
- 2. FINISH (EXCEPT SURFACE S1): BLACK ANODIZED


3. COATING (APPLY ACROSS CLEAR APERTURE) \$1: BARE GOLD R(AVG) >94% @ 0.7-0.8µm R(AVG) >97% @ 0.8-2.0µm R(AVG) >98% @ 2-12µm


SURFACE ROUGHNESS: <100 Å RMS


- 4. FOCAL LENGTH TOLERANCE: ±1%
- 5. ROHS COMPLIANT

FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING









## SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

REV. A	\$1	EFL	310.08		Edmund Ontice
SHAPE	PARABOLIC	PFL	304.80		Edmund Optics®
REFLECTIVE WAVEFRONT DISTORTION AT 632.8nm (RMS)	1λ	1			Ø50.8 X 310.08mm EFL 15° OAP BARE GOLD
SURFACE FIGURE AT 632.8nm (RMS)	λ/2	THIRD ANGLE PROJECTION	$\oplus \lhd$	TITLE	MIRROR 100Å
CLEAR APERTURE	90%		 		
BEVEL	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	35664 SHEET 1 OF 1