


## NOTES:


- 1. SUBSTRATE: CRYSTAL QUARTZ
- 2. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(ABS) <0.25% @ 1064nm DAMAGE THRESHOLD: 3.5 J/cm² @ 10ns @ 1064nm
- 3. SURFACE S1 TO BE PARALLEL TO SURFACE S2 TO WITHIN <0.5 arcsec
- 4. RETARDANCE:  $\lambda/4 \pm \lambda/200$
- 5. TRANSMITTED WAVEFRONT: λ/10 FOR CENTRAL 80% OF CLEAR APERTURE
- 6. Rohs Compliant











SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

| <b>Edmund Optics</b> | <b>)</b> ® |
|----------------------|------------|
|----------------------|------------|

| CLEAR APERTURE  | \$1<br>Ø46.0 | \$2<br>Ø46.0 | THIRD ANGLE<br>PROJECTION | THIRD ANGLE PROJECTION | TITLE     | 76.2mm DIA. 1064nm λ/4 QUAR<br>WAVEPLATE ZERO ORDER | TZ     |
|-----------------|--------------|--------------|---------------------------|------------------------|-----------|---|--------|
| CLEAR AFERTORE  | Ø40.0        | Ø46.0        |                           |                        | 51116116  |   | SHEET  |
| SURFACE QUALITY | 10-5         | 10-5         | ALL DIMS IN               | mm                     | mm DWG NO | NO 85062  | 1 OF 1 |