
## NOTES:


- 1. SUBSTRATE: CRYSTAL QUARTZ
- COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(abs) <0.25% @ 532nm DAMAGE THRESHOLD: 3.5 J/cm<sup>2</sup> @10ns @ 1064nm


*FOR INFORMATION ONLY:* DO NOT MANUFACTURE


PARTS TO THIS DRAWING

- 3. SURFACE \$1 TO BE PARALLEL TO SURFACE \$2 TO WITHIN <0.5 arcsec
- 4. RETARDANCE:  $\lambda/2 \pm \lambda/200$
- 5. TRANSMITTED WAVEFRONT:  $\lambda$ /10 FOR CENTRAL 80% OF CLEAR APERTURE
- 6. RoHS COMPLIANT









SECTION A-A

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

				<b>Edmund Optics</b> <sup>®</sup>		
CLEAR APERTURE	\$1 Ø8.0	\$2 Ø8.0	THIRD ANGLE	TITLE	12.7mm DIA. 532nm λ/2 QUARTZ WAVEPLATE MULTIPLE ORDER	
SURFACE QUALITY	10-5	10-5	ALL DIMS IN mm	DWG NO	85084	Sheet 1 OF 1