


NOTES:

**FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING**



1. SUBSTRATE: FUSED SILICA
2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN <3 ARCMIN
3. COATING (APPLY ACROSS COATING APERTURE):
 S1: R(ABS) > 99% @ 355nm
 T(ABS) > 95% @ 532nm @ 45° AOI



 DAMAGE THRESHOLD (PULSED):
 2.5 J/cm² @ 20ns , 20 Hz @ 355nm
 5 J/cm² @ 20ns , 20 Hz @ 532nm

 S2: R(ABS) < 0.25% @ 532nm @ 45° AOI

 DAMAGE THRESHOLD (PULSED):
 10 J/cm² @ 20ns , 20 Hz @ 532nm

4. FINE GRIND SURFACE

5. ROHS COMPLIANT




SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY



	S1	S2
SHAPE	PLANO	PLANO
SURFACE QUALITY	10-5	10-5
CLEAR APERTURE	Ø21.59	Ø21.59
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

THIRD ANGLE PROJECTION



ALL DIMS IN

mm

TITLE

Ø25.4mm HS 355R/532T HARMONIC BEAMSPLITTER

DWG NO

37719

SHEET 1 OF 1