## NOTES:

- 1. SUBSTRATE: ZERODUR
- 2. S2 TO BE PARALLEL TO S1 TO WITHIN <30 ARCSEC
- 3. COATING (APPLY ACROSS COATING APERTURE) \$1: ENHANCED ALUMINUM R(AVG) > 95% FROM 450-650nm @ 0° AOI


S2: NONE




- 5. CLEAR APERTURE AND COATING APERTURE ARE CENTERED ON SURFACE
- 6. SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE

ARROW ON EDGE POINTS TOWARDS 1/10TH WAVE SURFACE S1

8. ROHS: COMPLIANT





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2					
SHAPE	PLANO	PLANO				Edmund Opt	icc®
SURFACE QUALITY	20-10	COMMERCIAL POLISH				Edillalla Opt	102
SURFACE FLATNESS	0.10 WAVE	N/A		1		MIRROR 1/10 WV ZDUR EN AI 10	0.50
CLEAR APERTURE	9.00 x 9.00	N/A	THIRD ANGLE PROJECTION		TITLE	WIIIKKOK 1710 WW ZDOK EIWW 103Q	
COATING APERTURE	9.60 x 9.60	N/A		<u> </u>			CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	39847	SHEET 1 OF 1