
## NOTES:


- 1. SUBSTRATE: ZERODUR
- 2. S2 TO BE PARALLEL TO S1 TO WITHIN <30 ARCSEC
- 3. COATING (APPLY ACROSS COATING APERTURE) S1: PROTECTED GOLD R(AVG) > 96% FROM 700-2000nm @ 0° AOI R(AVG) > 96% FROM 2000-10000nm @ 0° AOI

S2: NONE

## FINE GROUND SURFACE /4.\

- 5. CLEAR APERTURE AND COATING APERTURE ARE CENTERED ON SURFACE
- 6. SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- ARROW ON EDGE POINTS TOWARDS 1/10TH WAVE SURFACE \$1 /7.\
- 8. ROHS: COMPLIANT





## *FOR INFORMATION ONLY:* DO NOT MANUFACTURE PARTS TO THIS DRAWING

## SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	S1	\$2			( <b>(</b> )	
Shape	PLANO	PLANO			Edmund Optics	<b>C</b> ®
SURFACE QUALITY	20-10	COMMERCIAL POLISH				2
SURFACE FLATNESS	0.10 WAVE	N/A			MIRROR 1/10 WV ZDUR GOLD 50 DIA	·
CLEAR APERTURE	Ø45.00	N/A	THIRD ANGLE	TITLE		
COATING APERTURE	Ø48.00	N/A				SULLET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	39868	Sheet 1 OF 1