


- SUBSTRATE
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO <10 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) METALLIC ND
- 4. FINE GROUND SURFACE
- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. Rohs Compliant

FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING










IR NEUTRAL DENSITY FILTER


REV. A	\$1	\$2	]	P	Edmund Optic	`C®
SHAPE	PLANO	PLANO				,S
SURFACE QUALITY	60-40	60-40				
CLEAR APERTURE	Ø22.5	Ø22.5	THIRD ANGLE PROJECTION	TITLE	OD 0.3, Ø25mm, IR NEUTRAL DENSITY FILTER	
COATING APERTURE	Ø10.00	N/A				CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	64353	SHEET 1 OF 1


- SUBSTRATE
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO <10 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) METALLIC ND
- 4. FINE GROUND SURFACE
- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. Rohs Compliant












IR NEUTRAL DENSITY FILTER


REV. A	\$1	\$2	]	P	<b>Edmund Optics</b>	<b>C</b> ®
SHAPE	PLANO	PLANO				<b>o</b>
SURFACE QUALITY	60-40	60-40				
CLEAR APERTURE	Ø22.5	Ø22.5	THIRD ANGLE PROJECTION	TITLE	OD 0.5, Ø25mm, IR NEUTRAL DENSITY FILTER	
COATING APERTURE	Ø10.00	N/A				CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	64354	SHEET 1 OF 1


- SUBSTRATE
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO <10 ARCMIN
- 3. COATING(APPLY ACROSS CLEAR APERTURE) METALLIC ND
- 4. FINE GROUND SURFACE
- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. Rohs Compliant












IR NEUTRAL DENSITY FILTER


REV. A	\$1	\$2			P	Edmund Option	C®
SHAPE	PLANO	PLANO					<i>-</i> 3
SURFACE QUALITY	60-40	60-40		1			
CLEAR APERTURE	Ø22.5	Ø22.5	THIRD ANGLE PROJECTION		TITLE	OD 1, Ø25mm, IR NEUTRAL DENSITY FILTER	
COATING APERTURE	Ø10.00	N/A					CHEET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	64355	SHEET 1 OF 1


- SUBSTRATE
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO <10 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) METALLIC ND
- 4. FINE GROUND SURFACE
- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. Rohs Compliant












IR NEUTRAL DENSITY FILTER


REV. A	S1 PLANO	S2 PLANO		8	<b>Edmund Optic</b>	CS®
SURFACE QUALITY	60-40	60-40	1			
CLEAR APERTURE	Ø22.5	Ø22.5	THIRD ANGLE PROJECTION	TITLE	OD 2, Ø25mm, IR NEUTRAL DENSITY FILTER	
COATING APERTURE	Ø10.00	N/A				CUEET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	64356	SHEET 1 OF 1


- SUBSTRATE
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO <10 ARCMIN
- 3. COATING(APPLY ACROSS CLEAR APERTURE) METALLIC ND
- 4. FINE GROUND SURFACE
- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. Rohs Compliant











IR NEUTRAL DENSITY FILTER

REV. A	\$1	S2	]			Edmund Optic	)C®
SHAPE	PLANO	PLANO					)S
SURFACE QUALITY	60-40	60-40		1			
CLEAR APERTURE	Ø22.5	Ø22.5	THIRD ANGLE PROJECTION		TITLE	OD 3, Ø25mm, IR NEUTRAL DENSITY FILTER	
COATING APERTURE	Ø10.00	N/A		 			CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	64357	SHEET 1 OF 1