
NOTES:


1. SUBSTRATE: **FUSED SILICA**


- 2. S2 TO BE PARALLEL WITH S1 TO WITHIN < 1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: NONE

FINE GRIND SURFACE

5. Rohs Compliant







PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

> SHEET 1 OF 1

SHAPE PLANO PLANO SUPPACE QUALITY 40.20			
		\$1	\$2
10 20 40 20	SHAPE	PLANO	PLANO
30KFACE QUALIT 40-20 40-20	SURFACE QUALITY	40-20	40-20
CLEAR APERTURE (mm) Ø11.25 Ø11.25	CLEAR APERTURE (mm)	Ø11.25	Ø11.25
PROTECTIVE AS NEEDED PROTECTIVE AS NEED	BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

			Edmund Optic	;S®
THIRD ANGLE PROJECTION	\$	TITLE	12.5mm DIA., 3mm THICK, UNCOATED FUSED SILICA WINDOW), λ/4
ALL DIMS IN	mm	DWG NO	14959	SHEET